



Lumistrips

DATASHEET

VIOLET900 UVC LED LIGHT 280NM 2780MW 36 LEDS 52X12DEG 48V 86W 89CM
3M CABLE

SKU: 44450.23




Article number (SKU)		44450.23	
Product name		Violet900 UVC LED Light, 280nm, 2780mW, 52 x 12° 36 LEDs, 3m cable	
Classification		Professional UV-C fixture	
Model identifier		Violet900 / approx. 890 mm optical body	
Optical data (reference conditions)			
Light colour		UVC	
Dominant wavelength		280 nm	
Radiant power		2780 mW @ Tc = 60 °C	
Beam angle FWHM		52° x 12°	
Typical LED lifetime / >70% flux		On request	
Electrical data			
Operating mode		Constant voltage	
Input voltage		30-50 V DC (48 V nominal)	
Input current		<1800 mA @ 48 V	
Power		<86 W @ 48 V	
Standby consumption		0.1 W	
Dimming / control		PWM + remote ON/OFF	
Electrical connection		3 m cable, open ends, 3 x 1.5 mm²	
Dimensions / mechanical data			
Overall length		924.5 ± 2 mm	36.398 in
Width		77.9 ± 1 mm	3.067 in
Height		59.4 ± 1 mm	2.339 in
Weight		Not specified in supplied Violet900 material	
Number of LEDs		36	
Heat dissipation		Free convection through housing	
Housing		Hard-anodized aluminium, 30 µm	
Optic		Stainless-steel frame / silicone optic	
Temperatures / humidity			
Operating temperature at Tc		-40 °C to +60 °C	
Ambient temperature		-40 °C to +35 °C	
Storage temperature		-40 °C to +80 °C	
Humidity		Max. 90%, non-condensing	
Approvals / protection			
CE / RoHS / REACH		Yes	
EN 62471 risk group		RG3	
IP rating		IP65	
Electrical protection class		III (SELV)	
Version			
Date		11 September 2026	

Notes: radiant power, beam angle and irradiance are simulation-derived values in the family datasheet and are specified with ±20% tolerance where applicable.



MECHANICAL DRAWING



Dimensions are in millimetres. The drawing applies to the Violet900 housing and standard mounting hardware.

MANUFACTURING INFO




We develop and manufacture LED modules, strips and integrated lighting assemblies in Hechingen, Germany, drawing on more than 20 years of experience in LED technology.



Our capabilities cover UV LED modules, optics, thermal design, control electronics and complete protected assemblies, with support from development and prototyping through to series production.

CUSTOM DEVELOPMENT AND SUPPORT

- Custom Violet600 options can include wavelength, optical distribution, supply/control interface and mechanical integration, subject to technical feasibility.
- Development support covers UV LED selection, optical simulation, thermal design, electronics and system integration.



Our manufacturing capabilities include surface-mount assembly, mechanical integration and final product assembly for protected LED fixtures. The production process is selected to suit the product design and volume.

PRODUCTION QUALITY

- Laser marking for product identification and traceability
- Solder paste inspection before component placement
- Automated component placement
- Controlled reflow soldering
- Three-dimensional automated optical inspection

Manufacturing management systems: ISO 9001 for quality, ISO 14001 for environmental management and ISO 45001 for occupational health and safety. These certifications apply to the manufacturing centre; product approvals are listed separately in the technical data.

UV LED SELECTION AND PERFORMANCE

Violet900 fixtures are configured by wavelength and optical system. This datasheet covers SKU 44450.23 with 280 nm UVC LEDs and the 50° x 10° optical distribution.



- Radiant power: 2780 mW at T_c = 60 °C.

VIOLET900 UVC LED LIGHT 280NM 2780MW 36 LEDS 52X12DEG 48V 86W 89CM 3M CABLE

- Beam angle: 50° x 10° FWHM.
- Typical L70 lifetime: on request.
- Installed irradiance depends on distance, temperature, alignment and the final application geometry.

OPTICAL PERFORMANCE - 280 NM

The wavelength-dependent graphs on this page apply to the 280 nm Violet900 variants. The irradiance values shown below are the values for SKU 44450.23.



Maximum irradiance, simulated at Tc = 60°C


Distance	250 mm	500 mm	1000 mm	1500 mm
Max. irradiance	15.65 mW/cm ²	3.91 mW/cm ²	0.98 mW/cm ²	0.43 mW/cm ²


1000 mm value from supplied SKU map; other distances scaled by inverse-square relationship.

Source note: wavelength and lifetime data are based on LED manufacturer data; simulation-derived optical values are specified with ±20% tolerance in the family datasheet.

OPTICAL DISTRIBUTION - SKU 44450.23

The exact 1000 mm irradiance simulation for SKU 44450.23 is included below. The product has a 52° x 12° optical distribution; the exact polar viewing-angle graphic was not supplied in this batch.






ELECTRICAL CONNECTION, PWM AND T_c

PWM DIMMING & ON/OFF CONTROL:

REMOTE ON/OFF [DIM]	If not used: Insulate; do not connect.
	Power ON with dimming: > 2.5 – 5 V DC or open.
	Power OFF: V _{in} < 0.8 V DC or GND
PWM frequency [DIM]	100 Hz – 1 KHz
Quiescent current [DIM]	2 mA with PWM OFF @ 48 V

Cable assignment 3x 1,5 mm², 3 m


- Brown: +V_{in}
- Blue: GND (-)
- Green/Yellow: DIM



If the DIM conductor is not used, isolate it and leave it unconnected. Power ON with dimming when the DIM input is >2.5-5 V DC or open; power OFF when the DIM input is <0.8 V DC or connected to GND.

Supported PWM frequency: 100 Hz to 1 kHz. Quiescent current at DIM when PWM is OFF: approximately 2 mA @ 48 V.

T_c is measured at the centre of the housing front, next to the optic, as indicated in the source drawing above.




POWER SUPPLY SELECTION

Use an electronically regulated DC supply within the 30-50 V input range. At the nominal 48 V reference, input current is approximately 1.8 A at full power and total input power is approximately 86 W. The supply must provide short-circuit, overload and overtemperature protection.

MOUNTING AND MECHANICAL INTEGRATION

The adjustable mounting brackets allow the fixture to be aimed through approximately 105° . Maintain sufficient clearance around the housing for free convection and do not obstruct the optical window or the Tc measurement area.

Overall length with standard mounting hardware is approximately 924.5 mm. The commercial Violet900 designation refers to the approximately 890 mm light-body length.



Housing: hard-anodized aluminium. Screws, star knobs and mounting brackets: stainless steel. Cable jacket: silicone. Optical frame: stainless steel; optic: silicone.

HANDLING, INSTALLATION AND UV SAFETY



Hazardous ultraviolet radiation - Risk Group 3.

- Operate the fixture only with the shielding, access control, interlocks and personal protective measures required for the application.
- Avoid direct, unprotected viewing of the optics or LEDs and prevent skin exposure.
- Disconnect the supply before installation, wiring, adjustment or service. Installation must be performed by a qualified electrician in accordance with applicable standards.
- Do not mechanically stress the fixture, optical window, cable or internal components. Do not overtighten fixings or bend the housing.
- Avoid aggressive chemicals during storage and operation. Maximum specified humidity is 90% non-condensing.
- The fixture is rated IP65; the complete installation must still be assessed for the intended environment and cleaning process.
- Before operation, check polarity, DIM wiring, cable termination, mounting, aiming, shielding and safety interlocks.

DOCUMENT INFORMATION

This individual datasheet is based on the supplied Violet900 mechanical drawings, optical-performance graphics, and SKU-specific 1000 mm irradiance simulation for SKU 44450.23. Only values directly supplied or explicitly derived from those materials are included.

We reserve the right to make technical changes.

ORDERING AND PRODUCT INFORMATION

www.ledrise.eu / www.lumistrips.com