


VIOLET-12X1-S

~20° wide beam when used with one UV LED

TECHNICAL SPECIFICATIONS:

Dimensions	294.8 x 41.6 mm
Height	8.8 mm
Fastening	screw
ROHS compliant	yes 


MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour	Finish
VIOLET-12X1-S	Multi-lens	Silicone	clear	
VIOLET-12X1-FRAME	Accessory	Stainless steel	metal	

ORDERING INFORMATION:

Component		Qty in box	MOQ	MPQ	Box weight (kg)
FN17294_VIOLET-12X1-S	Multi-lens	78	26	26	7.7
» Box size: 398 x 298 x 150 mm					







PHOTOMETRIC DATA (SIMULATED):




LED XT-E
FWHM 30.0°
Efficiency 86 %
Peak intensity 2.4 cd/lm
LEDs/each optic 1
Light colour White
Required components:




LED LTPL-G35UVC-GC
FWHM 46.0°
Efficiency 72 %
LEDs/each optic 1
Light colour UV
Required components:



LED LTPL-G35UVC-GR
FWHM 40.0°
Efficiency 72 %
LEDs/each optic 1
Light colour UV
Required components:




LED NCSU334A
FWHM 40.0°
Efficiency 72 %
LEDs/each optic 1
Light colour UV
Required components:



PHOTOMETRIC DATA (SIMULATED):


SAMSUNG

LED LM301B
FWHM 38.0°
Efficiency 88 %
Peak intensity 1.8 cd/lm
LEDs/each optic 1
Light colour White
Required components:




SEOUL VIOSYS

LED WICOP DY9560-27
FWHM 43.0°
Efficiency 66 %
LEDs/each optic 4
Light colour UV
Required components:



SEOUL VIOSYS

LED WICOP DY9560-27
FWHM 22.0°
Efficiency 72 %
LEDs/each optic 1
Light colour UV
Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)